

**Amendments to the Specification:**

Please replace the paragraph beginning at page 3, line 21, with the following rewritten paragraph:

5

-- The invention achieves the above-identified objects by providing a terminal structure of an electrical connector having continuous terminals and a connection material tape with projections respectively connected to the continuous terminals, which are formed by pressing a metal plate. Each terminal  
10 includes an extension having a first end and a second end, a connection having a first end connected to the first end of the extension and a second end formed with a to-be-broken portion connected to the projection, and a contact connected to the second end of the extension. The to-be-broken portion is broken to separate the terminal from the material tape. The contact has two elastic arms with a gap  
15 therebetween, and the two elastic arms have contact surfaces close to each other. The extension is horizontal and has a twisted portion to make the contact vertical so that the two contact surfaces of the contact may contact an inserted male terminal in vertical directions. --

20 Please replace the paragraph beginning at page 6, line 2, with the following rewritten paragraph:

-- Referring to FIGS. 6 and 7, a terminal structure of the invention ~~having has~~ continuous terminals 30 and a connection material tape 28 with projections 29 respectively connected to the continuous terminals 30, which are formed by  
25 pressing a metal plate. Each terminal 30 includes an extension 31, a connection 40, a contact 44 and a twisted portion 38. --

Please replace the paragraph beginning at page 6, line 9, with the following rewritten paragraph:

30 -- The connection 40 having a first end 41 connected to the first end 32 of the extension 31, and a second end 42 formed with a to-be-broken portion 43

Appl. No. 10/792,225  
Amdt. dated July 25, 2005  
Reply to Office action of 05/02/2005

connected to the projection 29 of the connection material tape 28, wherein the connection 40 is bent to form an angle of 90 degrees with the extension 31. The to-be-broken portion 43 is broken to separate the terminal 30 from the connection material tape 28 and is formed with a cutting mark to facilitate separating the  
5 terminal 30 from the connection material tape 28. --